

## KBSG 矿用防爆干式变压器

型号	额定容量 (KVA)	电压组合及分接范围			联结组标号	损耗 (W)		空载电流 (%)	短路阻抗 (%)	重量 (Kg)	外形尺寸 (mm) 长*宽*高		
		高压 (kv)	高压分接范围 (%)	低压 (KV)		空载	负载						
KBSG-50/6	50	6	±5	0.693/0.4	Yy0(d11)	350	550	2.5	4	1300	2100*700*900		
KBSG-100/6	100					520	920	2.5	4	1400	2150*720*1000		
KBSG-160/6	160					700	1300	2	4	1660	2210*762*1050		
KBSG-200/6	200					820	1550	2	4	1900	2260*760*1050		
KBSG-250/6	250					952	1800	2	4	2400	2400*780*1100		
KBSG-315/6	315					1100	2150	1.8	4	2800	2580*875*1340		
KBSG-400/6	400					1300	2600	1.8	4	3100	2650*900*1400		
KBSG-500/6	500					1500	3100	1.5	4	3510	2750*950*1485		
KBSG-630/6	630					1800	3680	4.5	4	3815	2750*950*1545		
KBSG-800/6	800					1.2/0.693	2050	4500	1.0	4	4975	2740*990*1560	
KBSG-1000/6	1000			3.45	2350	5400	1.0	4	5900	2950*1060*1615			
KBSG-1250/6	1250			1.2	2750	6500	1.0	4	6860	3000*980*1590			
KBSG-1600/6	1600			3.45	3350	8000	0.8	4	8650	3050*1175*1650			
KBSG-2000/6	2000			3.45	3800	9500	0.6	4.5	9150	3150*1190*1865			
KBSG-2500/6	2500				4500	10600	0.6	5	13000	3550*1200*1900			
KBSG-3150/6	3150				5300	12500	0.6	5.5	16000	3800*1250*1800			
KBSG-4000/6	4000				6100	14000	0.6	6	19000	3900*1300*1850			
KBSG-50/10	50				10	±5	0.693/0.4	Yy0(d11)	390	680	2.5	4	1400
KBSG-100/10	100			560					1050	2.5	4	1750	2350*800*1050
KBSG-160/10	160			800					1500	2	4	2150	2500*850*1300
KBSG-200/10	200	950	1800	2					4	2300	2500*850*1300		
KBSG-250/10	250	1100	2100	2					4	2580	2600*895*1400		
KBSG-315/10	315	1300	2500	1.8					4	2900	2730*895*1450		
KBSG-400/10	400	1500	3000	1.8					4	3210	2820*910*1500		
KBSG-500/10	500	1750	3500	1.5					4	3605	2960*950*1530		
KBSG-630/10	630	2000	4100	1.5					4	4630	2270*990*1585		
KBSG-800/10	800	1.2/0.693	2300	5100					1.2	4	5580	2950*1060*1615	
KBSG-1000/10	1000	3.45	2600	6100			1.2	4.5	6150	3020*1050*1680			
KBSG-1250/10	1250	1.2	3100	7400			1.0	4.5	6900	3140*1050*1790			
KBSG-1600/10	1600	3.45	3800	8500			1.0	5	8600	3380*1100*1850			
KBSG-2000/10	2000	3.45	4500	9700			0.7	5	11000	3590*1200*1900			
KBSG-2500/10	2500		5200	10800			0.7	5.5	14000	3750*1360*1735			
KBSG-3150/10	3150		6100	12800			0.7	5.5	18000	3700*1300*1800			
KBSG-4000/10	4000		7000	15000			0.7	6	21000	4180*1350*1900			

备注:可根据客户需求设计,本参数只做参考.